

# UNIVERGE® SV9300

## COMMUNICATIONS SERVER



### Smart Communications for **Small and Medium Businesses**

The **UNIVERGE SV9300 Communications Server** is a robust, feature-rich, Unified Communications system that is ideal for small and medium-sized businesses. The server is designed to help solve today's communications challenges and is built with your migration path in mind, so you can scale your communications as your business grows.

The SV9300 offers:

- > Distinct, scalable, Unified Communications server
- > IP or Digital voice support
- > Unified Messaging, Voicemail and Mobility features included
- > Streamlined application integration through the new simplified user licensing structure
- > Easy-to-use single point configuration and management
- > Stackable chassis architecture which supports server functions, media gateways and media converters in a single unit.



"The SV9300 will grow as your business grows."



#### At a Glance

- > Redundant CPU and power options
- > IP Extensions/Digital/Analog
- > Stations up to 2,048
- > 2,048 Resource Ports
- > Trunks up to 512
- > Multi-Line SIP Client with Multi-Carrier SIP Support

# The SV9300 meets all your communications needs.



## Technical Data

Item		1 Unit			2 Units	3 Units	4 Units	System Max				
		2U x 1	2U x 2	2U x 3	2U x 6	2U x 9	2U x 12	Standalone		Remote Unit		
<b>Blade Slots</b>		6	12	18	36	54	72	72		900		
<b>Port</b>	Physical Port	108	216	324	628	972	1296	1296	2048	2048	2048	
	Virtual Port	1536			2048			2048		2048		
<b>Physical Port</b>	SLT (-28V)	96	192	288	576	864	1152	1152	1536	1536	1536	
	SLT (-48V)	24	48	72	144	216	288	288		1536		
	Digital Multiline Terminal (-48V) (DT400/DT300 series)	96	192	288	576	864	1152	1152		1536		
	Digital Multiline Terminal (-48V) (DT400/DT300 series w/APR) <b>(Note 1)</b>	28 (28)	56 (56)	84 (84)	168 (168)	252 (252)	336 (336)	336 (336)		336 (336)		768 (768)
	DSS Console (for DT400/DT300 series) <b>(Note 2)</b>	32						32		32		32
	Desk Console <b>(Note 4)</b>	8						8		8		8
	ISDN Terminal (BRI Bch) <b>(Note 3)</b>	48	96	144	256			256		256		256
	In-skin UMS Port	48	96	128				128		128		128
16-Party Conference w/ PVA (ch)	96	128					128	128	128			
<b>Virtual Port</b>	IP Multiline Terminal (DT800/DT700 series)	1024			1536			1536	1536	1536		
	Softphone											
	Wi-Fi Handset (MH240)											
	IP Single Line Telephone (SIP) (Standard SIP Terminal)	512			1024			1024		1024		
DSS Console (for DT800/DT700 series) <b>(Note 2)</b>	32						32	32	32			
<b>Physical Port</b>	Central Office Trunk	COT	48	96	144	288	432	512	512	512	512	
		DID	24	48	72	144	216	288		288		
	Tie Line Trunk	E&M	24	48	72	144	216	288		288		512
	BRI Trunk <b>(Note 3)</b>		48	96	144	256				256		256
	PRI Trunk <b>(Note 6)</b>	23B+D	96	192	288	504				504		504
		30B+D	93	186	279	496				496		496
	DTI Trunk	T1	96	192	288	504				504		504
		E1	90	180	270	510				510		510
CCIS Trunk <b>(Note 6)</b>	1.5M	96	192	288	384			384	384			
	2M	93	186	279	496			496	496			
<b>Virtual Port</b>	IP Trunk (P2P CCIS)	512						512	512	512		
	SIP Trunk <b>(Note 8)</b>	100			200	300	400	400	512			

# The SV9300 meets all your communications needs.



## Technical Data (cont.)

Item		1 Unit			2 Units	3 Units	4 Units	System Max		
		2U x 1	2U x 2	2U x 3	2U x 6	2U x 9	2U x 12	Standalone	Remote Unit	
VoIP Channel	w/RTP	128			256	384	512	512	6400	
SIP Converter		96			192	288	384	384	384	
Modem Channel (Note 4)		1						1	1	
Speech Synthesis announcement (Note 4)		8						8	16	
VRS Message (Note 4)		16						16	16	
DTMF Sender		64						64	64	
Caller ID Sender (FSK)		16						16	16	
DTMF Receiver (Note 5)		32						32	32	
MF Sender (Note 4, 5)		32						32	32	
MF Receiver (Note 5)		32						32	32	
Caller ID Receiver (FSK) (Note 5)		32						32	32	
Caller ID Receiver (DTMF) (Note 5)		32						32	32	
MFC Sender (Note 5)		16						16	16	
MFC Receiver (Note 5)		16						16	16	
3-/4-Party Conference (ch)		64			128				128	128
32-Party Conference (ch) (Note 7)		32						32	32	

**Note 1:** When using DT400/DT300/Dterm with APR (Dual Port Mode), the physical ports for analog station shown in parenthesis are required in addition to the physical ports for Multiline Terminal.

**Note 2:** The total number of following DSS Consoles is maximum 32 per system.

- DSS Console (for DT400/DT300 series)
- DSS Console (for DT800/DT700 series)

**Note 3:** The required number of ports per blade is shown in Table 4-2. (e.g. GCD-2BR1A +GPZ-2BR1A: 8 ports)

**Note 4:** Available at main unit (Unit01) only.

**Note 5:** The total number of following functions is maximum 32 per system.

- DTMF Receiver
- Caller ID Receiver (FSK)
- Caller ID Receiver (DTMF)
- MFC Sender
- MFC Receiver
- MF Sender
- MF Receiver

**Note 6:** The number of System Port Capacity Licenses required is different from the number of actual Physical Ports consumed. Refer to Table 8-2.

**Note 7:** The following conference groups can be configured.

- One, 32-party conference group
- Two, 16-party conference groups
- Four, eight-party conference groups

**Note 8:** In case of call from/to TDM terminal via SIP trunk, maximum 512 calls (100 calls per unit) can be established at the same time, because one VoIPDB channel is occupied per call. In case of call from/to IP terminal via SIP trunk, maximum 50 calls can be established at the same time, because two VoIPDB channels are occupied per call.



For further information please contact your local NEC representative or:

**Corporate Headquarters (Japan)**  
NEC Corporation  
www.nec.com

**North America (USA & Canada)**  
NEC Corporation of America  
www.necam.com

**NEC Enterprise Solutions**  
NEC Europe Ltd  
www.nec-enterprise.com

**APAC**  
NEC Asia Pacific Pte Ltd  
sg.nec.com

**Latin America**  
NEC Latin America  
www.lasc.necam.com

**About NEC Corporation of America** Headquartered in Irving, Texas, NEC Corporation of America is a leading provider of innovative IT, network and communications products and solutions for service carriers, Fortune 1000 and SMB businesses across multiple vertical industries, including Healthcare, Government, Education and Hospitality. NEC Corporation of America delivers one of the industry's broadest portfolios of technology solutions and professional services, including unified communications, wireless, voice and data, managed services, server and storage infrastructure, optical network systems, microwave radio communications and biometric security. NEC Corporation of America is a wholly-owned subsidiary of NEC Corporation, a global technology leader with operations in 44 countries and more than \$32.6 billion in revenues. For more information, please visit [necam.com](http://necam.com).



HW14014 | v.10.01.14 © 2014 NEC Corporation. All rights reserved. NEC, NEC logo, and UNIVERGE are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All trademarks identified with ® or ™ are registered trademarks or trademarks respectively. Models may vary for each country.